




Vi-Link

Fiber Optic Communications

8 Channels High Quality 3G HD-SDI Broadcast Video Over SM One Fiber

CCTV Equipment Series

Model DL800



Product Description

Vi-Link HD SDI Video equipment: The DL800 is a fiber optic digital multiplexer that designed to transmit up to 8 channels of high quality uncompressed digital 3G HD SDI video signals over one single mode cable. It is a cost effective selection for transporting high quality SDI camera pictures from the remote location to the operation center via long fiber optic cable. The DL800 is compatible with all SMPTE rates: *SMPTTE259M SDI from 143 to 360 Mbps, SMPTTE344M 540Mbps, SMPTTE292M HD-SDI 1.485 Gbps, SMPTTE372M Dual Link HD-SDI 2,97 Gbps, SMPTTE424M Dual Speed 3G-SDI 2.97 Gbps.*

The DL800 offers a fully serial digital video encoding/decoding of real time high quality digital video providing adjustment free operation over a wide operational range. Using automatic gain control and state-of-the-art multiplexing, combining with CWDM technologies for distances from back-to-back to 50 Kilometers, our digital signaling offers superior receiver output stability, which is unaffected by changes in fiber path attenuation due to aging or splicing points.

The extended temperature capability of the DL800 satisfies very critical applications requiring high quality video performance with high reliability.

Applications include Broadcast Video Production, Video Editing, Unmanned Aircraft Vehicle Days & Nights Monitoring Systems, ITS Intelligent Traffic System, Metro & Railroad Monitoring System, Homeland Security, Utility Management, Premise Networks, Military Hardened applications or anything requiring HD quality video performance.

Features

- 8 Channels High Quality Digital Broadcast Video System
- Single Mode Fiber With CWDM Technology
- Real Time High 3G-HD-SDI Video
- Compatible with all SMPTE3G SDI Rates
 - SMPTTE259M SDI from 143 to 360 Mbps, SMPTTE344M 540Mbps,
 - SMPTTE292M HD-SDI 1.485 Gbps, SMPTTE372M
 - Dual Link HD-SDI 2,97 Gbps,
 - SMPTTE424M Dual Speed 3G-SDI 2.97 Gbps
- AGC Single mode Transmission of 0 to 50 Km
- 90~240 VAC or +24 VDC, +28 VDC, -48 VDC
- NEMA Temperature

Applications

- Broadcasting Video Transmission
- High Quality HD-SDI Video Monitoring in Traffic Control Center
- METRO Security System
- Unmanned Aircraft Video System
- Oil & Gas Perimeter Intruder Detection
- Military Applications
- Premise Networks
- Any High Quality Video Requirement

Ordering Information

Model	Descriptions
DL800TST03	8 Channels 3G HD SDI (Video Tx) SM ST, 50Km, 90~240 VAC@0.5Amp
DL800RST03	8 Channels 3G HD SDI (Video Rx) SM ST, 50Km, 90~240 VAC@0.5Amp

*** Please Consult Factory for Additional Model Numbers***



Vi-Link

Fiber Optic Communications

Technical Specifications


HDTV Equipment Series

Model DL800

System:	
Error Rate	1 in 10 ¹² or Better
Indicators	PWR, CH1 .. CH8
Optical:	
Transmitter	CWDM Lasers
Tx	1470nm~1610nm
Receiver	PIN
Rx	1470nm~1610nm
Power Budget	20 dB @ SM
Connector	ST
Environment:	
Operating	-34 ⁰ C to +74 ⁰ C
Storage	-40 ⁰ C to + 95 ⁰ C
Humidity	98% Non-Condensing

3G HD-SDI Video Interface:	
Channel	8 x 3G HD-SDI
Format	SMPTE 259M, 292M and 424M
Speed	143M~540M, 1.485GB~2.97 GB
Full HD Revolution	1280 x 720P @ 50/60fps 1920 x 1080P @ 50/60fps
Signal Level	800mVp-p +/-10%
Connector	BNC
Impedance	75 Ohms
Physical:	
Dimensions	19" x 10" x 1.75"
Weight	7 lbs
Power:	
AC	90~240 VAC @ 0.5Amp 50/60Hz
DC	+24 VDC, +28VDC, -48 VDC

Application



Typical DL800T & DL800R Application