



Product Description

The MC10 Unmanaged Media Converter series is designed to operate in high temperature NEMA environment with 1 x 10/100/1000Mbps copper port 1 and 1 x 1000 Base-SX Fiber Optic Ethernet Port. The converter mediates between a 10/100/1000M Base-TX segment and a 1000Base-SX segment. It is primarily designed for large, higher speed/bandwidth demanding workgroups that require expansion of the Ethernet network. It can extend the conventional 10M Ethernet, 100M Fast Ethernet or 1000M Ethernet to 20Km~100Km via the Gigabit Ethernet Fiber-optical Line. It is high-performance, cost effective and flexible solutions for a wide range of applications in the field of LAN campus network.

With the Web-based management MC1600 chassis, the MC10 will offer an easy-to-use and configuration facility, via the WEB interface, it can be programmed for basic management functions such as per port speed duplex settings, Port Trunking, VLAN, Port Mirroring, network security authentication and misc configurations. Additionally, the firmware includes advanced features such as IGMP snooping, QoS (Quality of Service), broadcast storm and bandwidth control, to enhance bandwidth utilization. The extended temperature capability for meeting NEMA specifications satisfies very critical applications requiring high quality data transmission performance with high reliability.

Applications include ITS Intelligent Traffic System, Metro Operation, HDTV Broadcasting System, IP cameras Surveillance, Homeland Security, Utility Management, Premise Networks, Military Hardened applications or anything requiring high speed Ethernet Network performance.

Features

- 1 1000Mbps SFP
- 1 Port 10/100/1000Mbps RJ45
- Automatic MAC address learning and aging
- Automatically support IGMP (Multicasting)
- 10/100/1000Mbps Auto-negotiation , auto-MDI-MDI-X
- Transmission Distance Up to 50 Km with Single Mode Fiber
- LED indicators for monitoring power/link/activity
- Supports 10/100/1000Mbps-Full/Half-duplex
- Supports Wall-mount and DIN-Rail installation
- Supports Daisy-Chain connection
- Supports Broadcast Storm Control
- NEMA operating temperature range

Applications

- ITS Traffic Applications
- SCADA Networks
- Metro Networks
- Gas & Oil Fields Monitoring Applications
- Railroad Networks
- Military Applications
- Data Acquisition Applications

Ordering Information

Model	Descriptions
MC10LC03	Fiber Optic Industrial Media Converter, 10/100/1000M, LC (SFP Port), SM 50Km, +5 VDC
MC10RLC03	Fiber Optic Industrial Media Converter 10/100/1000M, Rack Card , SC (SFP Port), SM 50Km
	*** Replace LC with SC for SC Connector***

Network TV Equipment Series

Model MC10

System:	
Error Rate	1 in 10 ¹² or Better
Network Standard	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3z FX IEEE 802.3x Flow Control IEEE 802.3ad Port trunk with LACP IEEE 802.3w RSTP IEEE 802.1Q VLAN Tagging
Indicators	PWR, TP, FO, 100M
Ports	1 x 10/100Base-T 1x 100Base- FX
Frame Flow Control	Full Duplex Mode
Frame size	16K Bytes
Jumbo Frame	9000 Bytes
Layer 2 Management	Store-and Forward Remote Monitoring (RMON) Far-end Fault Indication (FEFI) Link Fault Pass Through (LFP) Auto Recovery Remote Management and Set Up Manual IP Address Setting / DHCP Loopback, Broadcast, Multicast, Unicast storm control Speed Duplex Mode Configuration Bandwidth Control on TP/FX
Physical:	
Dimension	4.2" x 2.7" x 1.0"
Power	+5 VDC @1 Amp

Fiber Interface:	
Port	1 x 1000Base-FX
Data Rate	100 Mbps
Connector	LC or SC
Distances	10KM@1310MM, 50KM@1310SM
TX Interface:	
TX Port	1 x 10/100/1000Base-TX Auto-Negotiation MDI/MDIX
Data Rate	10/100/1000 Mbps
Connector	RJ45
Transmission Mode	Half/Full Duplex
Network Management :	
Interface	Web Browser, SNMPv1, v2c Monitor
Port Configuration	Port enable, Auto-Negotiation, Full and Half Duplex mode, Flow Control Enable, Bandwidth Control
VLAN	16 IEEE 802.1Q VLAN / Q-in-Q VLAN
Link Aggregation	Supports IEEE 802.3ad LACP
QoS	802.1p Priority, DSCP field in IP
IGMP Snooping	IGMP (v1/v2) Snooping, up to 64 Multicast groups
SNMP MIBs	RFC-1213 MIB-2, RFC-1573 MIB RFC-2819 RMON MIB (Group 1)
Environment:	
Operating	-34 ^o C to +74 ^o C
Storage	-40 ^o C to + 95 ^o C
Humidity	98% Non-Condensing

Application

